

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In Re Application of:
JOSEPH HONEIN

§
§
§
§
§
§

Atty File: IM 1725

Serial No.: FILED

PRIOR Group Art Unit: 3634

Filed: HEREWITH

PRIOR Examiner: A. CHIN SHUE

For: COMPOSITE SCAFFOLDING PLANK AND METHOD OF FORMING SAME

PRELIMINARY AMENDMENT

Assistant Commissioner for Patents
Washington, D.C. 20231

Sir:

This amendment is presented prior to examination. Please enter the following amendments:

IN THE CLAIMS:

CANCEL CLAIMS 1-10 WITHOUT PREJUDICE AND

ADD NEW CLAIMS:

15.(NEW) A method for forming a scaffolding plank from two or more wooden boards, comprising:

positioning a plurality of wooden boards in side to side abutment, each of said wooden boards including two sides and a lengthwise direction, each of said sides being flat and having a height and said height being the smallest dimension of said wooden boards;

compressing said plurality of wooden boards vertically so that the top surfaces of said plurality of wooden boards are co-planar and concurrently compressing said plurality of wooden boards transversely before revolvingly embedding at least three spaced apart helical pins;

positioning a drill at a lateral outside edge of said plurality of wooden boards and a pin press at an opposite outside edge of said plurality of wooden boards:

said drill having a drilling axis;

said pin press having a pin press axis;

said drilling axis and said pin press axis substantially aligned;

drilling holes transversely through said plurality of wooden boards

revolvingly embedding said at least three spaced apart pins transversely through said plurality of wooden boards by forcing said helical pins through said holes, normal to said sides of said plurality of wooden boards, and normal to said lengthwise direction of said plurality of wooden boards, each of said at least three spaced helical pins having helical threads said helical pins having an outer thread diameter and further having a root thread diameter, said drilled hole having a hole diameter; and said hole diameter greater than said thread root diameter and less than said outer thread diameter; and

subsequently removing the compression on said plurality of wooden boards;

whereby said drilling step and said forcing step are sequentially performed while said plurality of wooden boards are laterally and vertically compressed and the helical threads of said plurality of helical pins become anchored within each of said wooden boards thereby fixing and maintaining said wooden boards in relative position.

16.(NEW) A method as in claim 15 further comprising aligning said plurality of

wooden boards such that their ends form a substantially continuous surface before revolvingly embedding said at least three spaced helical pins.

17.(NEW) A method as in claim 15 further comprising:

each of said at least three spaced helical pins is a twist lock pin having a square cross section.

18.(NEW) A method of increasing the strength of a wooden scaffolding plank comprising the steps of:

cutting said plank longitudinally into a plurality of wooden plank sections;

positioning said plurality of wooden plank sections in side to side parallel abutment with the wood grains of said plurality of wooden plank sections having alternating directions, each of said wooden plank sections including two sides and a lengthwise direction, each of said sides being flat and having a height and said height being the smallest dimension of said wooden plank sections;

compressing said plurality of wooden boards vertically so that the top surfaces of said plurality of wooden boards are co-planar and concurrently compressing said plurality of wooden boards transversely before revolvingly embedding at least three spaced helical pins;

positioning a drill at a lateral outside edge of said plurality of wooden boards;

said drill having a drilling axis;

a pin press having a pin press axis;

said drilling axis and said pin press axis substantially aligned;

drilling holes transversely through said plurality of wooden boards, said helical pins having an outer thread diameter and further having a root thread diameter,

[illegible]

said drilled holes having a hole diameter; and

said hole diameter being greater than said thread root diameter and less than said outer thread diameter;

revolvingly embedding said at least three spaced helical pins transversely through said plurality of wooden plank sections by forcing said helical pins through said holes, normal to said sides of said plurality of wooden plank sections, and normal to said lengthwise direction of said plurality of wooden plank sections, each of said at least three spaced helical pins having helical threads; and

subsequently removing the compression on said plurality of wooden boards;

whereby said drilling step and said forcing step are sequentially performed while said plurality of wooden boards are laterally and vertically compressed and the helical threads of said at least three spaced helical pins become anchored within each of said plurality of wooden plank sections thereby fixing and maintaining said wooden plank sections in relative position.


19.(NEW) A method as in claim 18 further comprising aligning said plurality of wooden plank sections such that their ends form a substantially continuous surface before revolvingly embedding said at least three spaced helical pins.

20.(NEW) A method as in claim 18 wherein each of said at least three spaced helical pins is a twist lock pin having a square cross section.

REMARKS

Variable	Mean	SD	Min	Max
Age	34.5	10.2	22	55
Gender	0.5	0.5	0	1
Marital status	0.6	0.5	0	1
Education	12.5	1.5	10	15
Income	1500	500	1000	2500
Health status	0.8	0.2	0	1
Employment status	0.7	0.3	0	1
Family size	3.2	1.1	1	5
Home ownership	0.9	0.1	0	1
Vehicle ownership	0.6	0.5	0	1
Insurance coverage	0.8	0.2	0	1
Financial literacy	0.7	0.3	0	1
Investment experience	0.5	0.5	0	1
Asset diversity	0.6	0.4	0	1
Debt-to-income ratio	0.3	0.2	0	1
Emergency fund	0.4	0.3	0	1
Retirement savings	0.5	0.4	0	1
Charitable giving	0.2	0.2	0	1
Overall financial health	0.6	0.3	0	1

Respectfully submitted,



Kenneth H. Johnson
Attorney of Record

Kenneth H. Johnson
Attorney of Record
Reg. No. 22,966
P.O. Box 630708
Houston, Texas 77263
Tel.: (713) 780-7047
Fax: (713) 780-7671
E-mail: john7820@aol.com

CERTIFICATE OF MAILING

I hereby certify that this correspondence is being deposited with the United States Postal Service as first class mail in an envelope addressed to:

Assistant Commissioner for Patents
Washington, D.C. 20231

on

11/19/01

251

Kenneth W. H.

CLEAN COPY OF NEW CLAIMS

15.(NEW) A method for forming a scaffolding plank from two or more wooden boards, comprising:

positioning a plurality of wooden boards in side to side abutment, each of said wooden boards including two sides and a lengthwise direction, each of said sides being flat and having a height and said height being the smallest dimension of said wooden boards;

compressing said plurality of wooden boards vertically so that the top surfaces of said plurality of wooden boards are co-planar and concurrently compressing said plurality of wooden boards transversely before revolvingly embedding at least three spaced apart helical pins;

positioning a drill at a lateral outside edge of said plurality of wooden boards and a pin press at an opposite outside edge of said plurality of wooden boards:

said drill having a drilling axis;

said pin press having a pin press axis;

said drilling axis and said pin press axis substantially aligned;

drilling holes transversely through said plurality of wooden boards

revolvingly embedding said at least three spaced apart pins transversely through said plurality of wooden boards by forcing said helical pins through said holes, normal to said sides of said plurality of wooden boards, and normal to said lengthwise direction of said plurality of wooden boards, each of said at least three spaced helical pins having helical threads said helical pins having an outer thread diameter and further having a root

CLEAN COPY OF NEW CLAIMS

thread diameter, said drilled hole having a hole diameter; and said hole diameter greater than said thread root diameter and less than said outer thread diameter; and

subsequently removing the compression on said plurality of wooden boards;

whereby said drilling step and said forcing step are sequentially performed while said plurality of wooden boards are laterally and vertically compressed and the helical threads of said plurality of helical pins become anchored within each of said wooden boards thereby fixing and maintaining said wooden boards in relative position.

16.(NEW) A method as in claim 15 further comprising aligning said plurality of wooden boards such that their ends form a substantially continuous surface before revolvingly embedding said at least three spaced helical pins.

17.(NEW) A method as in claim 15 further comprising:
each of said at least three spaced helical pins is a twist lock pin having a square cross section.

18.(NEW) A method of increasing the strength of a wooden scaffolding plank comprising the steps of:

cutting said plank longitudinally into a plurality of wooden plank sections;
positioning said plurality of wooden plank sections in side to side parallel abutment with the wood grains of said plurality of wooden plank sections having alternating directions, each of said wooden plank sections including two sides and a lengthwise direction, each of said sides being flat and having a height and said height being the smallest dimension of said wooden plank sections;

CLEAN COPY OF NEW CLAIMS

compressing said plurality of wooden boards vertically so that the top surfaces of said plurality of wooden boards are co-planar and concurrently compressing said plurality of wooden boards transversely before revolvingly embedding at least three spaced helical pins;

positioning a drill at a lateral outside edge of said plurality of wooden boards;

said drill having a drilling axis;

a pin press having a pin press axis;

said drilling axis and said pin press axis substantially aligned;

drilling holes transversely through said plurality of wooden boards, said helical pins having an outer thread diameter and further having a root thread diameter, said drilled holes having a hole diameter; and said hole diameter being greater than said thread root diameter and less than said outer thread diameter;

revolvingly embedding said at least three spaced helical pins transversely through said plurality of wooden plank sections by forcing said helical pins through said holes, normal to said sides of said plurality of wooden plank sections, and normal to said lengthwise direction of said plurality of wooden plank sections, each of said at least three spaced helical pins having helical threads; and

subsequently removing the compression on said plurality of wooden boards;

whereby said drilling step and said forcing step are sequentially performed while said plurality of wooden boards are laterally and vertically compressed and the helical

CLEAN COPY OF NEW CLAIMS

threads of said at least three spaced helical pins become anchored within each of said plurality of wooden plank sections thereby fixing and maintaining said wooden plank sections in relative position.

19.(NEW) A method as in claim 18 further comprising aligning said plurality of wooden plank sections such that their ends form a substantially continuous surface before revolvingly embedding said at least three spaced helical pins.

20.(NEW) A method as in claim 18 wherein each of said at least three spaced helical pins is a twist lock pin having a square cross section.

FOR THE